

# Floor Maintenance & Cleaning Specification

## Polysafe- Wetroom Floorcare Information



### General Guidelines:

Polysafe (Hydro • Hydro Evolve • Quattro) Wetroom Safety Vinyl Sheetting is manufactured with aggregates throughout the product to improve traction and safety underfoot. The product features a high quality cross-linked polyurethane reinforcement and **should not be sealed**.

**NOTE:** We highly recommend an effective barrier/entrance matting system to reduce the dirt tracked into the building.

### Daily Maintenance:

1. Remove all dust, sand and stones from the floor using a vacuum cleaner.
2. Spot mop wet sticky dirt with a double/single bucket mopping unit using a **Vileda Safe Mop** and the correct dilution of neutral detergent such as **Proclean**.
3. For larger areas, the floor can be washed using a **Nilfisk Automatic Scrubber-Drier, Prolene Brush** and **Proslip** low foam neutral detergent.
4. For kitchens, a food safe chemical such as **Diner-gen** degreaser should be used for mopping and/or scrubbing.

**Note:** Only a Prolene brush should be used to scrub the floor.

### Recommended Products:



**Vileda Microfibre  
Flat Mopping Unit  
with Safe Mop**



**Proclean  
Neutral  
Detergent**



**Diner-gen  
Food safe  
Degreaser**



**Nilfisk Low Speed  
Scrubber &  
Prolene Brush**



**Nilfisk Autoscrubber  
with Prolene Brush**

## **Periodic Cleaning**

For high traffic or heavily soiled areas the floor can be deep cleaned periodically

1. Remove all dust, sand and stones from the floor using a vacuum cleaner.
2. Scrub the floor using a **Low Speed Scrubber** fitted with a **Prolene Brush**.
3. For light to medium soiling, a solution of **Proclean** neutral detergent can be used for scrubbing. For heavily soiled areas, **Proflex** diluted according to manufacturer's instructions can be used. For detail work, a hand brush with prolene bristles can be used.
4. Vacuum the dirty chemical solution from the floor with a **Wet & Dry Vacuum Cleaner**.
5. Rinse the floor thoroughly with clean water to remove any remaining chemical residue.
6. If no machine is available, remove the solution from the floor using a mop and mopping system. The water and mop must be changed frequently so as to remove as much of the chemical residue as possible.

**Note:** Only a Prolene brush should be used to scrub the floor. The floor must be thoroughly rinsed with clean water after stripping to neutralize the area.

## **Recommended Products:**



**Nilfisk VL500 Wet & Dry  
Vacuum Cleaner**



**Proclean  
Neutral  
Detergent**



**Proflex  
Degreaser**



**Nilfisk Low Speed  
Scrubber &  
Prolene Brush**

---

## **Cleaning of Equipment:**

1. All equipment should be cleaned thoroughly after use.
2. Pads should be rinsed or vacuumed depending on soiling.
3. Single disc machines must be wiped with a damp cloth and disinfectant if needed.

For more information on the above cleaning methods please contact 011 801 4600 or [info@industroclean.co.za](mailto:info@industroclean.co.za).