

Hard-wearing synthetic rubber floor tile with a low-profile studded surface, available in a choice of contemporary colours. Renowned for durability and comfort underfoot and making a beneficial contribution to impact sound reduction, it is ideal where long life under heavy traffic is required.



SaarFloor Noppe Stud Tile

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	3.0mm
Total Weight	ISO 23997 (EN 430)	4200g/m²
Performance Requirements		
General Performance	EN 12199	Conforms
Use Area	ISO 10874 (EN 685)	23, 32, 41
Slip Resistance	EN 13893 AS 4586	Class DS R9
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 (EN 433)	<0.25mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.30%
Underfloor Heating		Suitable, max 27°C
Cigarette Resistance	EN 1399	Method A Rating >4 Method B Rating >3

Sustainability	
BRE Green Guide	A+ Generic
Recyclable	100%
REACH	Compliant
Indoor Air Comfort Gold	Eurofins certified product
AqBB/ABG	Pass

Acoustic Performance		
Impact Sound Reduction	ISO 10140-3	8dB

Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.		

Tile Size

Format	Size	Shades	Quantity per Box	Coverage per Box
Tile	500mm x 500mm	12	20	5m²


SaarFloor Noppe Stud Tile

GROUP 1




Black Coal **101**
NCS S 8502-R

LRV 5




Anthracite **102**
NCS S 8000-N

LRV 10




Steel **014**
NCS S 5502-G

LRV 21




Deep Blue **191**
NCS S 7020-B

LRV 7



Limestone Green **013**
NCS S 5010-B70G


LRV 22



Green Baize **015**
NCS S 6030-G10Y

LRV 8

GROUP 2




Mercury **129**
NCS S 3005-B80G

LRV 39



Warm Red **012**
NCS S 2070-Y90R

LRV 12




Orange **010**
NCS S 2070-Y50R

LRV 22




Cobalt **019**
NCS S 7020-R80B

LRV 7



Cool Blue **707**
NCS S 5020-B

LRV 18



Sandstone **140**
NCS S 3020-Y20R

LRV 34

LRV - Light Reflectance Value

NCS - Natural Colour System