

High performance vinyl sheet sports floor covering available in a choice of solid colours and contemporary wood effects. A multi-use sports floor for general sporting activities in a 6.7mm gauge, the range complies with EN 14904 and meets both Sport England and Sport Scotland requirements.



Sport 67

Technical Specification





Product Format		
Gauge	ISO 24346 (EN 428)	6.7mm
Total Weight		3600g/m²
Performance Requirements		
General Performance	EN 14904	Conforms
Sliding Coefficient of Friction	EN 13036	80 - 110
Shock Absorption	EN 14808	Pass
Ball Rebound	EN 12235	Pass
Vertical Deformation	EN 14809	Pass
Reaction to Fire	EN 13501-1 CAN/ULC S102.2	Class Cfl-S1 FSV < 300; SDV < 500
Abrasion Resistance	EN 649 ISO 5470-1	Group T <1000mg
Impact Resistance	EN 1517	Pass
Resistance to Indentation	EN 1516	Pass
Specular Gloss	ISO 2813	≤30%
Rolling-Load Resistance	EN 1569	Pass

Sheet Size

Format	Size	Shades	Coverage per Roll
Sheet	2m x 18.5m	4	37m²

Sustainability		
Recyclable		100%
Recycled Content		24%
FloorScore		Certified
Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
Polyflor Sport 67 is reinforced with polyurethane for improved cleaning and maintenance. Polyflor Sport 67 should not have a polish applied.		

Sport 67

			
Green 7515 NCS S 5030-G10Y	Blue 7512 NCS S 5030-R90B	Oak 7518 NCS S 4030-Y40R	Maple 7516 NCS S 3030-Y20R
w/r 7515 LRV 18	w/r 7512 LRV 15	w/r 7518 LRV 22	w/r 7516 LRV 37



LINE MARKINGS (width & colours)

Contact Polyflor for recommended line marking installers



50mm 



40mm 



50mm 



50mm 



50mm 

