

SPECIFICATION SHEET
NO:

PSA
39

DESCRIPTION:

POLYCLAD PRO & PLUS PU
WALL/CEILING CLADDING

DATE:

AUG
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install Polyclad Pro PU/Polyclad Plus PU, wall and ceiling cladding flexible PVC sheeting in 1.25mm/2mm thickness, homogeneous and monolayer in construction, fully tested to EN 13501-1 and installed with Polyflor recommended contact adhesive which has been spread using an A2 notched trowel on a previously prepared primed plastered wall, joints must be butted, U-shape grooved and heat welded using Polyflor's matching welding rod ensuring that the welding rod bonds to more than 2/3rds of the sheet in thickness, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07