

Specification Sheet No

PSA  
59

Description

CS48  
CAPPING STRIP

Date

MARCH  
2023

## ARCHITECTURAL SPECIFICATION / BOQ

### SPECIFICATION:

Supply and install fully flexible CS48 capping strip (35mm x 17mm) to finish off coved Polyflor sheeting to a pre-determined height up the wall determined with a level line using a gauge/dumpy level, easy to clean, needs no painting and offers long-term maintenance savings, ensuring a neat finish and continuous, sealed surface.

Colour:

Code:

### INSTALLATION: (PLEASE NOTE: ALWAYS USE COMPATIBLE PRODUCTS FROM ONE SUPPLIER)

Ensure that all surfaces are firm, dry, and free of dust, grease, and oil. All painted surfaces must be stripped back and wire brushed to remove all traces of paint.

Always observe the adhesive manufacturer's instructions. Pay attention to use of solvent-based adhesives, especially regarding ventilation and possible sources of ignition.

Accurate marking out is essential to minimise adhesive usage and to prevent wastage. Marking out may be done by a variety of methods including scribes, height gauges and section templates. All fitting work must be carried out accurately prior to application of adhesive, as movement afterwards is restricted. Adjustments for length should always be made on straight joints – never on mitred sections – unless the length of the wall does not permit this.

Apply Polyflor recommended contact adhesive to both surfaces, allow adhesive to flash off and then adhere capping strip to wall. Apply pressure to create a firm bond.

### MAINTENANCE:

Excess adhesive can be removed with an appropriate solvent such as Polyflor Powerclean if necessary. As a principle, aggressive solvents should be avoided as these may affect the capping strip, leaving dull spots). More powerful detergents such as PRO-INOX from Industroclean can be used to remove persistent soiling which is not removed by the initial clean.

Two coats of a matt sealer such as Proflor HM can be applied to as per the manufacturer's instructions.

Wipe with a damp cloth where required using a neutral detergent such as PROCLEAN.

We recommend that professional maintenance product suppliers be approached to determine the specific maintenance requirements for the application. Industroclean (Sean Harms) who supply the Pro range of products can be contacted directly on 083 400 7778.

**This program will keep maintenance costs to a minimum.**

## SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: [marketing@polyflor.co.za](mailto:marketing@polyflor.co.za) | [www.polyflor.co.za](http://www.polyflor.co.za)  
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07