

SPECIFICATION SHEET
NO:

PSA
68

DESCRIPTION:

ECOsurfaces 3.2mm
SHEETING

DATE:

AUG
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install install 3.20mm thick x 1.22m ECOsurfaces non-laminated, single-ply, rubber surface sheeting made from a formulation of high quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with multiple coloured reprocessed ColorMill EPDM rubber, manufactured in accordance with ASTM standards and installed with a Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, rolling the installed planks/tiles in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted joined, available from Polyflor (011) 609 3500.

Colour:

Code:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07