Sport 67

PRODUCT SPECIFICATION



Key Features

- > Hard-wearing vinyl sports floor
- > Wood designs & solid colours available
- > Sheet format in 6.7mm gauge
- > Conforms to EN14904
- > For use in 'multi-purpose' indoor sports arenas



Product Format	Standard	Result		
Gauge	ISO 24346 (EN 428)	6.7mm		
Total Weight		3600g/m²		
Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 18.5m	4	-	37m²
Performance Requirements	Standard	Result		

Performance Requirements	Standard	Result		
General Performance	EN 14904	Conforms		
Sliding Coefficient of Friction	EN 13036	80 - 110		
Shock Absorption	EN 14808	Pass		
Ball Rebound	EN 12235	Pass		
Vertical Deformation	EN 14809	Pass		
Reaction to Fire	EN 13501-1 CAN/ULC S102.2	Class Cfl-S1 FSV < 300; SDV < 500		
Abrasion Resistance	EN 649 ISO 5470-1	Group T <1000mg		
Impact Resistance	EN 1517	Pass		
Resistance to Indentation	EN 1516	Pass	Pass	
Specular Gloss	ISO 2813	≤30%	≤30%	
Rolling-Load Resistance	EN 1569	Pass		

Sustainability	Standard	Result
Recyclable		100%
Recycled Content		24%
FloorScore		Certified

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

 $Polyflor\,Sport\,67\,is\,reinforced\,with\,polyure thane\,for\,improved\,cleaning\,and\,maintenance.\,Polyflor\,Sport\,67\,should\,not\,have\,a\,polish\,applied.$











Sport 67

RANGE SHADES









Blue **7512** w/r 7512 NCS S 5030-R90B LRV 15



Oak **7518** w/r 7518 NCS S 4030-Y40R LRV 22



Maple **7516** NCS S 3030-Y20R

w/r 7516 LRV 37

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System