

Specification Sheet No

TDS
24

Description

BOX CHANNEL FOR VINYL
SHEETING – 50mm VO

Date

APRIL
2022

TECHNICAL DATA SHEET

Polyflor POL VCH 60mm Box Channel available with a vertical outlet in three lengths.

- POL VCV 500
- POL VCV 700
- POL VCV 900

Benefits:

- Available in 1.4301 (304) or 1.4404 (316L) grades of stainless steel, pickled and passivated
- Anchors for fixing in concrete
- Flexible installation due to rotatable and adjustable gully
- Recessed grating for improved drainage
- Integrated FAT for easy maintenance
- Suitable for public areas due to locked grating
- Borderless drainage solutions –Easy accessibility

Product information:

- Drain body DN50 / DN30 *available on request*
- Drain body can be rotated 360°
- Suitable for all push fit pipe socket systems
- Water sealant height: 50 mm
- Slotted grating of stainless steel (*Custom designs available on request*)
- Designed for perfect application with vinyl sheeting
- Load class: K 3
- Brushed silk gloss grating
- Locked grating

Flange design

- Location flange

Description:

- For vinyl sheet flooring
- With clamping flange
- With slotted grating
- Grating top 527mm x 98mm

Flow rate:

- 0.46(l/s)

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07
Directors: DL Coleman, P du Plessis, T Coleman, A Mc Lardy

