



SaarFloor Noppe Stud Tile

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	3.0mm
Total Weight	ISO 23997 (EN 430)	4200g/m²
Performance Requirements		
General Performance	EN 12199	Conforms
Use Area	ISO 10874 (EN 685)	23, 32, 41
Slip Resistance	EN 13893 AS 4586	Class DS R9
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 (EN 433)	<0.25mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.30%
Underfloor Heating		Suitable, max 27°C
Cigarette Resistance	EN 1399	Method A Rating >4 Method B Rating >3

Sustainability	
BRE Green Guide	A+ Generic
Recyclable	100%
REACH	Compliant
Indoor Air Comfort Gold	Eurofins certified product
AqBB/ABG	Pass

Acoustic Performance		
Impact Sound Reduction	ISO 10140-3	8dB

Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.		

Tile Size

Format	Size	Shades	Quantity per Box	Coverage per Box
Tile	500mm x 500mm	12	20	5m²

SaarFloor Noppe Stud Tile

GROUP 1



Black Coal **101**
NCS S 8502-R

LRV 5



Anthracite **102**
NCS S 8000-N

LRV 10



Steel **014**
NCS S 5502-G

LRV 21



Deep Blue **191**
NCS S 7020-B

LRV 7



Limestone Green **013**
NCS S 5010-B70G

LRV 22



Green Baize **015**
NCS S 6030-G10Y

LRV 8

GROUP 2



Mercury **129**
NCS S 3005-B80G

LRV 39



Warm Red **012**
NCS S 2070-Y90R

LRV 12



Orange **010**
NCS S 2070-Y50R

LRV 22



Cobalt **019**
NCS S 7020-R80B

LRV 7



Cool Blue **707**
NCS S 5020-B

LRV 18



Sandstone **140**
NCS S 3020-Y20R

LRV 34

LRV - Light Reflectance Value

NCS - Natural Colour System