

TECHNICAL SPECIFICATIONS: COMMERCIAL KITCHENS

TECHNICAL DATA	STANDARDS	Polysafe Apex	Polysafe Ultima
----------------	-----------	---------------	-----------------

Product Format

Gauge	ISO 24346 (EN 428)	2.5mm	2.5mm
Sheet Size	ISO 24341 (EN 426)	2m x 20m	2m x 20m
Total Weight	ISO 23997 (EN 430)	3150g/m ²	3000g/m ²

Performance Requirements

General Performance	EN 13845	Conforms	Conforms
	ASTM F1303	Type II, Grade I, Class B Backing	Conforms
Use Area	ISO 10874 (EN 685)	23, 34, 43	23, 34, 43
Enhanced Slip Resistance	EN 13845	ESf	ESb & ESf
	RRL Pendulum Test	>45 (wet test - 4S Rubber / Slider 96)	≥40 (wet test - 4S Rubber / Slider 96) ≥36 (wet test - TRL Rubber/Slider 55)
	DIN 51097 / DIN EN 16165 Ann. A	-	Class B
	DIN 51130 / DIN EN 16165 Ann. B	R12	R11
	ASTM D2047	SCOF≥0.8	-
Abrasion Resistance	EN 13845	50,000 cycles	50,000 cycles
	EN 13893	Class DS	Class DS
Reaction to Fire	EN 13501-1	Class Bfl-S1	Class Bfl-S1
	ASTM E648	Class 1	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500	-
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'	≤2.0kV Classified as 'antistatic'
Water Tightness	EN 13553	-	Annex A

Sustainability

BRE Green Guide		A+ ENP 472	A+ ENP 472
Indoor Air Comfort Gold		Eurofins certified product	Eurofins certified product
FloorScore		Certified	Certified
Finnish M1		Certified	Certified
AgBB/ABG		Pass	Pass
Responsible Sourcing	BES 6001	Excellent	Excellent

Maintenance Performance

Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance	Good resistance
-------------------------	--------------------	-----------------	-----------------

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to Health & Safety Executive (HSE) guidelines.

SAFETY FLOORING



Products in this category are designed to offer maximum slip resistance in extreme conditions, due to continuous contamination of the floor.